

InvisiLED® Pro


24V LED Tape Light

WAC LIGHTING

Responsible Lighting®



Tape Section



3 LED "L" Connector

Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Professional grade white tape light that delivers optimal color consistency and brightness. An ideal system for task or accent lighting applications.

FEATURES

- Ultra thin profile at 3/8"
- Diodes spaced evenly at 1" on center
- Minimum run length of 1'
- May be field cut every 2" at the end of a run
- Three mounting methods provided for different surfaces
- Specially rated for installation in the storage area of a clothes closet
- 50,000 hour rated life
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Flexible, silicone cased tape light. Peel and stick 3M construction adhesive on back. Indicating marks on back for field cutting.

Power Supply: Remote and plug-in electronic Class 2 transformers. 120VAC 50/60Hz input, 24V 60W and 96W output.

Light Source: 12 LEDs per foot


Dimming: May be dimmed with electronic low voltage (ELV) dimmer.

Operating Temp: -4°F – 122°F (-20°C – 50°C), relative humidity 95%.

Standards: UL & CUL Listed for damp locations.

ORDER NUMBER – TAPE SECTION

Model	Watts/ft	Color Temp	CRI	Lumens/ft	Length	Qty	Tape Color
LED-T24	3	W 2700K	85	200	2IN 2 inches	1	WT White
		P 3000K	85	200	2IN-10 2 inches	10	
		35 3500K	85	207	1 1 foot	1	
		C 4500K	85	215	1-40 1 foot	40	
					5 5 feet	1	




LED-T24___-___-WT

Example: **LED-T24P-2IN-10-WT**

ORDER NUMBER – 3 LED "L" CONNECTOR

Model	Watts	Color Temp	CRI	Lumens	Tape Color
LED-T24	1.2	W 2700K	85	50	3L-WT White
		P 3000K	85	50	
		35 3500K	85	52	
		C 4500K	85	54	



LED-T24___-3L-WT

Example: **LED-T24C-3L-WT**

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

InvisiLED® Pro

24V LED Tape Light

WAC LIGHTING

Responsible Lighting®

Class 2 Power Supply (Required)

Type		Model	Input	Output	Max Run	Dim	
Remote		EN-2460-RB2-T	120VAC	24VAC / 60W	20 feet	ELV	Includes a 6 foot lead wire
		EN-24100-RB2-T	120VAC	24VAC / 96W	33 feet	ELV	
Plug-in		EN-2460-P-AR-T	120VAC	24VAC / 60W	20 feet	ELV	Includes a 6 foot lead wire
		EN-24100-P-AR-T	120VAC	24VAC / 96W	33 feet	ELV	
Remote 277V		EN-24100-277-RB2-T	277VAC	24VDC / 96W	33 feet	0-10V	Includes a 6 foot lead wire

Accessories

Aluminum Channel		LED-T-CH	5 feet	Includes a diffuser, two end caps, and five screws				
Deep Aluminum Channel		LED-T-CH1	5 feet	Includes a diffuser, two end caps, and five screws				
45° Angled Aluminum Channel		LED-T-CH2	5 feet	Includes a diffuser, two end caps, and ten screws				
Fixed Angle Channel Clip		LED-T-CL3-PT	5 feet	Used to mount any aluminum channel Includes 2 pieces, 4 screws				
Adjustable Channel Clip		LED-T-CL2-PT	5 feet	Used to mount any aluminum channel Adjusts 50° from center either way Includes 2 pieces, 4 screws				
Retrofit Channel		LED-T-RC	3 feet	Creates fixed curves				
Clip		LED-T-CL	10 pcs	Holds the tape from the underside Includes 10 pieces, 10 screws				
Curve Clip		LED-T-CL1	10 pcs	Runs over the tape to secure the angled tape Includes 2 pieces, 4 screws				
Lead Wire		LED-TC-P-2	Black	2 ft	Alternative lengths for plug-in power supplies			
		LED-TC-P-2-WT	White	2 ft				
		LED-TC-P-12	Black	12 ft				
		LED-TC-P-12-WT	White	12 ft				
Extension Cable		LED-TC-EXT-144	Black	12 ft	Extends distance between a hard wired power supply or wiring box to a tape section			
		LED-TC-EXT-144-WT	White	12 ft				
Low Voltage Wiring Box With Feed		LED-TC-B-2 LED-TC-B-2-WT	Black White	L: 1½" W: ¾" H: ⅞"	Neatly houses up to two wires with 2" female feed			
Low Voltage Wiring Box		LED-T-B	White	L: 1½" W: ¾" H: ⅞"	Neatly houses up to two wires			
Wiring Box With Switch		TB-S	White	L: 6¼" W: 1⅝" H: 1¼"	Use when spanning a large gap in a system layout without leaving exposed wiring			
Joiner Cable		LED-TC-IC2	Black		LED-TC-IC2-WT	White	2 in	Connects tape sections
		LED-TC-IC6	Black		LED-TC-IC6-WT	White	6 in	
		LED-TC-IC12	Black		LED-TC-IC12-WT	White	12 in	
		LED-TC-IC36	Black		LED-TC-IC36-WT	White	36 in	
		LED-TC-IC72	Black		LED-TC-IC72-WT	White	72 in	
3-Way "Y" Connector		LED-TC-Y LED-TC-Y-WT	Black White	Connects tape sections				
4-Way "X" Connector		LED-TC-X LED-TC-X-WT	Black White	Connects tape sections				
"L" Connector		LED-TC-L LED-TC-L-WT	Black White	Connects tape sections				
End cap		LED-TC-EC LED-TC-EC-WT	Black White	1 cut end cap and 1 male end cap				
Male to male connector		LED-TC-MM	Black	50 Qty				